

AMENDMENTS TO THE CLAIMS:

Please cancel Claims 16 through 28, 45 through 57, and 59 without prejudice to or disclaimer of the subject matter recited therein.

Please amend Claims 1, 2, 6, 9 through 11, 29, 30, 34, 37 through 39, and 58 as follows:

1. (Currently Amended) A method for the insertion of information for the control of the broadcasting of a data stream in a heterogeneous network, the heterogeneous network including at least one entry sub-network conveying first packets and a basic network conveying second packets, the entry sub-network being connected to the basic network by means of an entry node forming the second packets from at least one sub-part of at least one first packet, wherein the entry node:

[[ - ]] receives first packets from the entry sub-network;

[[ - ]] associates an access level with each first packet from a plurality of access levels, as a function of a predetermined policy of association;

[[ - ]] forms each second packet by enclosing at least a first packet or part of a first packet into said second packet, the first packets or part of the first packets enclosed within the second packet being associated with a same access level;

[[ - ]] for each second packet, inserts into a field of the second packet representing the broadcast control information, the same access level associated with the at least first packet or part of a first packet enclosed within the second packet; and

[[ - ]] transmits the second packets formed into the basic network.

2. (Currently Amended) A method according to claim 1 wherein, at each change in access level, between a first packet associated with a previous access level and another first packet associated with a new access level, the entry node:

[[ -]] forms a synchronization second packet such that the start of the payload information of the synchronization second packet corresponds to the start of the payload information of the first packet associated with the new access level; and

[[ -]] inserts a synchronization marker in the synchronization second packet, [[ :]]

3. (Original) A method according to claim 2, wherein the entry node modifies the size of each second packet preceding one of the synchronization second packets, in such a way that no filler element is necessary to complete said preceding second packet.

4. (Original) A method according to claim 3, wherein the entry node modifies the size of the synchronization second packet, so that the sum of the modified size of the preceding second packet and the modified size of the synchronization second packet is substantially equal to the normal size of a second packet.

5. (Original) A method according to claim 2, wherein the entry node manages a mechanism, put into effect at each change in access level, for obtaining a current distance in memory, between a stored position of a forthcoming start of a first packet and a current position of a read pointer used for the construction of the second packets.

6. (Currently Amended) A method according to claim 5, wherein the entry node performs the following steps:

[[ -]] the entry node obtains said current distance;

[[ - ]] if the current distance is equal to zero, the entry node generates and sends a synchronization second packet for which the start of the payload information corresponds to the start of the payload information of a first packet associated with the new access level, this synchronization second packet comprising a synchronization marker;

[[ - ]] if the current distance is smaller than the normal size of a second packet, the entry node generates and sends a truncated second packet, known as a preceding second packet, whose reduced size is equal to the current distance, and then generates and sends a synchronization second packet for which the start of the payload information corresponds to the start of the payload information of a first packet associated with the new access level, this synchronization second packet comprising a synchronization marker; and

[[ - ]] if the current distance is greater than or equal to the normal size of the second packet, the entry node sends a normal-sized second packet which is not a synchronization second packet.

7. (Original) A method according to claim 2, wherein, at each change in access level, the entry node also inserts an access level change marker into the synchronization second packet.

8. (Original) A method according to claim 1, wherein the policy of association of an access level with each first packet is based upon restriction on the use of the data stream and wherein the access level comprises use restriction information.

9. (Currently Amended) A method according to claim 1, wherein the policy of association of an access level with each first packet is based on the use of a plurality of time slots, and wherein the entry node:

[[ -]] obtains the time slot, among said plurality of time slots, that includes the instant of processing, by the entry node, of the given first packet; and

[[ -]] associates one of the access levels with the first packet as a function of the time slot obtained.

10. (Currently Amended) A method according to claim 1, wherein the policy of associating an access level with each first packet is based on the use of a plurality of pieces of control information that can be contained in the first packets, and wherein the entry node:

[[ -]] obtains at least one piece of control information, from among said plurality of pieces of control information, contained in a given first packet; and

[[ -]] associates one of the access levels with the given first packet as a function of said at least one piece of control information obtained.

11. (Currently Amended) A method according to claim 8, wherein the policy of associating an access level with each first packet is based on the use of said plurality of time slots and said plurality of pieces of control information, and wherein the entry node:

[[ -]] obtains the time slot, among said plurality of time slots, that includes the instant of processing, by the entry node, of a given first packet;

[[ -]] obtains at least one piece of control information, from among said plurality of pieces of control information, contained in a given first packet; and

[[ -]] associates one of the access levels with the given first packet as a function of the time slot obtained and said at least one piece of control information obtained.

12. (Original) A method according to claim 1, wherein the data stream is transmitted by an entry terminal and wherein the entry terminal is a digital type of terminal

connected to the entry sub-network and directly generating the data stream in the form of first packets.

13. (Original) A method according to claim 1, wherein the data stream is transmitted by an entry terminal and wherein the entry terminal is an analog type terminal, connected to the entry sub-network by means of an independent adapter enabling the conversion, into first packets, of the data stream generated in the form of analog signals by the entry terminal.

14. (Original) A method according to claim 1, wherein the data stream is transmitted by an entry terminal and wherein the entry terminal is an analog type terminal directly connected to the entry node and wherein the entry node integrates an adapter enabling the conversion, into first packets, of the data stream generated in the form of analog signals by the entry terminal.

15. (Original) A method according to claim 1, wherein the data stream is transmitted by an entry terminal and wherein the entry terminal is integrated into the entry node and the entry node directly generates the data stream in the form of first packets.

16 - 28. (Cancelled)

29. (Currently Amended) An entry node for the insertion of information for the control of the broadcasting of a data stream transmitted in a heterogeneous network, the heterogeneous network including at least one entry sub-network conveying first packets and said basic network conveying second packets, the entry node being connected to the basic network and to the entry sub-network, wherein the entry node comprises:

[[ -]] means for receiving first packets from the entry sub-network;

[[ -]] means for the association of an access level with each first packet from among a plurality of access levels, as a function of a predetermined policy of association;

[[ -]] means for the formation of each second packet by enclosing at least a first packet or part of a first packet into said second packet, the first packets or part of the first packets enclosed within the second packet being associated with a same access level;

[[ -]] means for the insertion into a field of each second packet, said field representing the broadcast control information, the same access level associated with the at least first packet or part of a first packet enclosed within said second packet; and

[[ -]] means for the transmission of second packets into the basic network.

30. (Currently Amended) An entry node according to claim 29<sub>1</sub> comprising:

[[ -]] means for the detection of a change in access level, between a first packet associated with a previous access level and another first packet associated with a new access level;

[[ -]] means for the formation of a synchronization second packet such that the start of the payload information of the synchronization second packet corresponds to the start of the payload information of the first packet associated with the new access level; and

[[ -]] means for the insertion of a synchronization marker in the synchronization second packet.

31. (Original) An entry node according to claim 29, comprising means to modify the size of each second packet preceding one of the synchronization second packets, in such a way that no filler element is necessary to complete said preceding second packet.

32. (Original) An entry node according to claim 31, comprising means to modify the size of the synchronization second packet, so that the sum of the modified size of the preceding second packet and the modified size of the synchronization second packet is substantially equal to the normal size of a second packet.

33. (Original) An entry node according to claim 30, comprising means, activated at each change in access level, for the management of a mechanism to obtain a current distance in memory, between a stored position of a forthcoming start of a first packet and a current position of a read pointer used for the construction of the second packets.

34. (Currently Amended) An entry node according to claim 33, comprising means of selective activation as a function of the value of the current distance obtained, such that:

[[ - ]] if the current distance is equal to zero, the activation means activate means for the generation and sending of a synchronization second packet for which the start of the payload information corresponds to the start of the payload information of a first packet associated with the new access level, this synchronization second packet comprising a synchronization marker;

[[ - ]] if the current distance is smaller than the normal size of a second packet, the activation means activate means for the generation and sending of a truncated second packet, known as a preceding second packet, whose reduced size is equal to the current distance, and then means for the generation and sending of a synchronization second packet for which the start of the payload information corresponds to the start of the payload information of a first packet associated with the new access level, this synchronization second packet comprising a synchronization marker; and

[[ -]] if the current distance is greater than or equal to the normal size of the second packet, the activation means activate means for the sending of a normal-sized second packet which is not a synchronization second packet.

35. (Original) An entry node according to claim 30, comprising means for the insertion, at each change in access level, of an access level change marker into the synchronization second packet.

36. (Original) An entry node according to claim 29, wherein the policy of association of an access level with each first packet is based upon restriction on the use of the data stream and wherein the access level comprises use restriction information.

37. (Currently Amended) An entry node according to claim 29, wherein the policy of association of an access level with each first packet is based on the use of a plurality of time slots, and wherein the entry node comprises:

[[ -]] means for obtaining the time slot, among said plurality of time slots, that includes the instant of processing, by the entry node, of the given first packet; and

[[ -]] means for associating one of the access levels with the first packet as a function of the time slot obtained.

38. (Currently Amended) An entry node according to claim 29, wherein the policy of associating an access level with each first packet is based on the use of a plurality of pieces of control information that can be contained in the first packets, and wherein the entry node comprises:

[[ -]] means for obtaining at least one piece of control information, from among said plurality of pieces of control information, contained in a given first packet; and



[[ -]] means for associating one of the access levels with the given first packet as a function of said at least one piece of control information obtained.

39. (Currently Amended) An entry node according to claim 37, wherein the policy of associating an access level with each first packet is based on the use of said plurality of time slots and said plurality of pieces of control information, and wherein the entry node comprises:

[[ -]] means for obtaining the time slot, among said plurality of time slots, that includes the instant of processing, by the entry node, of a given first packet;

[[ -]] means for obtaining at least one piece of control information, from among said plurality of pieces of control information, contained in a given first packet; and

[[ -]] means for associating one of the access levels with the given first packet as a function of the time slot obtained and said at least one piece of control information obtained.

40. (Original) An entry node according to claim 29, wherein the entry node is directly connected to a entry terminal of analog type , which transmits the data stream and wherein the entry node integrates an adapter enabling the conversion, into first packets, of the data stream generated in the form of analog signals by the entry terminal.

41. (Original) An entry node according to claim 29, wherein the entry node comprises an entry terminal, which transmits the data stream and wherein the entry node comprises means for the direct generation of the data stream in the form of first packets.

42. (Original) An entry node according to claim 29, wherein the heterogeneous network is a home audiovisual network.

43. (Original) An entry node according to claim 29, wherein the first packets are IEEE 1394 type packets.

44. (Original) An entry node according to claim 29, wherein the basic network is a switched network.

45 - 57. (Cancelled)

58. (Currently Amended) A storage medium storing a computer program instructions for programming a programmable processing apparatus to become configured as an apparatus as set out in ~~any~~ claim 29 ~~or 45~~.

59. (Cancelled)